

HEX Drum filter

The right choice for fresh- & saltwater! Designed in Denmark. Manufactured in Germany.

Best Aquaculture Practice for more than 30 years

The innovative HEX | Drum filter has a unique HEX | BeeCell filter panel designed for reliable and efficient water filtration and removal of particles from 10 to 500 micron. HEX | Drum filter is simply best practice in water treatment for aquaculture businesses and show aquariums worldwide.





HEX | Concept – key features

- Direct Driven Gear Wheels (DDGW). Unique and very robust gear wheels in high-tech polymer lubricated by the filtered water.
- Sludge tray, dual slope ensures easy slide of sludge to discharge pipe.
- Backwash, ceramic nozzles covering the full drum length. HEX | IC - Intelligent Control monitors the back washing.
- Non-corrosive materials: Cover, motor box, tank and sludge tray are fully made of life lasting HDPE. Drum is made of POM, special PVC & HDPE (Model X) or AISI 304/316 (Model F, FW/ SW)

Designed in Denmark. Manufactured in Germany.

- CM Aqua strive to be a reliable partner for our customers.
- Our product range includes various parts of aquaculture equipment: drum filters, protein skimmers, biological filters.
- We are very proud of our internal Danish engineering team and German manufacturing facilities, that enables us to adapt our products to each customers individual needs.

HEX X-series



Innovative drum design

- Fully made of high-tech polymer
- Fast and accurate filter panel fixture
- 100 % balanced drum
- Light weight and corrosion free
- Increased capacity and deeper submersion

High quality bearings

- Lubricated by water
- Made of ceramic
- Solid life lasting rollers made of non-corrosive POM replacing a central shaft

Durable drum and frame

- Made of high-tech polymer
- For RAS, flow through systems and aquaculture ponds
- For de-licing, wellboats, stun and bleed boats and slaughterhouses

- Game-changing design from Denmark and manufactured in Germany
- Market leading filtration with HEX | BeeCell filter panel
- Non-corrosive even in warm saltwater

- Smooth operation with low maintenance
- Water and energy saving with HEX | IC
- Excellent support from our biologists and engineers

Over 1400 installations in more than 50 countries



HEX X-series



HEX | Drum filter X-series TANK

TAINK			
Description	Size	Filter Area	Capacity*
Description:	X1	0.46 m ²	10–50 m³/h
Closed version with the drum mounted in a tank with	X2	0.92–5.52 m ²	25–740 m³/h
connection for fast and easy installation. The tank can	Х3	4.41-12.42 m ²	116–1,400 m³/h
have an internal bypass depending on the water flow.	X4	7.36–16.56 m ²	224–1,900 m³/h
	X5	13.0-36.80 m ²	396–3,000 m³/h

* Depending on filter area, micron and TSS

406-5,000 m³/h

* Depending on filter area, micron and TSS

13.0-36.80 m²



HEX Drum filte HALF-T			
Description	Size	Filter Area	Capacity*
Description: Half-closed version for flexible mounting in the system. The inlet can be made as open channel or with pipe inlet. The outlet is open, but with a level	X1	0.46 m ²	10–84 m³/h
	X2	0.92–5.52 m ²	25–740 m³/h
	Х3	4.41–12.42 m ²	116–1,400 m³/h
	X4	7.36–16.56 m ²	231–3,000 m ³ /h
tank protecting the filter.	VE	$13.0.36.00 \text{ m}^2$	$100 - 5000 \text{ mm}^3/\text{h}$



HEX | Drum filter X-series CHANNEL INSTALLED

X5

		<u> </u>	
Description: Open version with the high-tech polymer drum mounted in an open frame for building into a channel installation.	Size	Filter Area	Capacity*
	X1	0.46 m ²	10–84 m³/h
	X2	0.92–5.52 m ²	25–740 m³/h
	Х3	4.41-12.42 m ²	116–1,400 m³/h
	X4	7.36–16.56 m ²	231–3,000 m³/h
	X5	13.0-36.80 m ²	406–5,000 m³/h

* Depending on filter area, micron and TSS

HEX F-series ... for regular and special purposes!



HEX | Drum filter F-series

Description:

Open version with the AISI 304/316 drum mounted in an open AISI 304/316 frame for building into a channel installation.

Size	Filter Area	Capacity*
F4	7.36–16.56 m ²	179–3,520 m³/h
F5	13.80-36.80 m ²	336–8,736 m³/h

* Depending on filter area, micron and TSS



HEX | Drum filter F-series

Description:

The SANI model has the drum mounted with a special connector for fast and simple installation. The SANI is designed for easy desinfection with ultra fast drain and full access to the drum's interior.

HEX | Drum filter F-series

Description:

Half-closed version for flexible mounting in the system. The inlet can be made as open channel or with pipe inlet. The outlet is open, but with a level tank protecting the filter.

Size	Filter Area	Capacity*
F4	7.36–16.56 m ²	179–3,520 m³/h
F5	13.80–36.80 m ²	336–8,736 m ³ /h

* Depending on filter area, micron and TSS



HEX | Drum filter F-series

Description:

The SHIP model has no cover and the drum is mounted in an open frame for building into wellboat tanks. The filter is designed with a drum holder for rough sea, ready for automatic desinfection.



Want to know more about HEX | Drum filter?

Contact us!

CM Aqua Technologies DTU Science Park Agern Allé 5A 2970 Hørsholm Denmark

> +45 2117 5600 info@cmaqua.dk

